TURB-O-K-VAC



- 1 Hydraulic truck load kit is easily set for all trucks and semis.
- 2 Hinged cyclone eliminates lifting, provides narrow transport & easy set-up.
- 3 Heavy duty frame, Tor-Flex axles, highway tires and fenders.
- 4 New belt drive on high capacity, positive displacement blower.
- 5 Easy to service dust removal system.
- 6 Rear entry receiver lets you see the unloading spout from inside bin.
- 7 Large capacity receiver tank for cleaning out drills and air seeders.

ALIGATOR NOZZLE

Clean-up nozzle with 18" mouth
Rides on two sets of casters
Ultra-Flexible 5 inch hose
Made of aluminum
Comes standard wih all Turb-O-K-Vacs
Can also be used with other vacs



ADRIAN MFG., INC.

191 120th
Newton, KS 67114
Office- 620-877-7239
Cell- 507-381-9746
admfg15@gmail.com
www.adrianmfg.com

The TURB-0-K-VAC system moves the grain from intake to discharge entirely by air. During operation, grain and air enter at the receiver cyclone and are separated. The air is drawn upward in a cyclone action which creates a TURBO ACTION precleaner separation system. The dust removal system then removes an additional 70% of the lighter dust before it passes through the blower. The grain, being heavier than air, swirls around the smooth interior of the receiver cyclone down to the airlock. The blow-through airlock meters the grain into the bottom blow-through pipe which conveys the grain through the discharge pipe.

A system conveying diagram is shown:

